

MARINE BLOWER



We manufacture a selection of marine blowers in a strong anti-shock abs homologated by R.I.N.A and with different capacity from 280 m3 to 1000 m3 per hour. Screws and shaft in stainless steel. Flexmount and very strong dynamic Flangemount. Low current draw. Best ratio on the market between volume air flow and compact size. All models are ignition protected ISO 8846.

FLANGE MOUNT



CAPACITY: 280 mc. per hour / 163 cfm
DIMENSIONS: 200 x 165 x 195 mm
PORT CONNECTIONS: Inlet: 75 mm - Outlet: 72 mm
CD. 5500001212 12 V. Amp 3,9
CD. 5500001224 24 V. Amp 2,5

CAPACITY: 550 m3 per hour / 324 cfm
DIMENSIONS: 290 x 257 x 150 mm
PORT CONNECTIONS: Inlet: 110 mm - Outlet: 103 mm
CD. 5500101212 12 V. Amp 11,5
CD. 5500121224 24 V. Amp 7,0



CAPACITY: 750 m3 per hour / 441 cfm
DIMENSIONS: 290 x 257 x 150 mm
PORT CONNECTIONS: Inlet: 150 mm - Outlet: 103 mm
CD. 5500101412 12 V. Amp 19
CD. 5500101424 24 V. Amp 11

CAPACITY: 1000 m3 per hour / 589 cfm
DIMENSIONS: 290 x 257x 180 mm
PORT CONNECTIONS: Inlet: 150 mm - Outlet: 103 mm
CD. 5500101624 24 V. Amp 16

FLEX MOUNT



CAPACITY: 550 m3 per hour / 324 cfm
DIMENSIONS: 290 x 257 x 150 mm
PORT CONNECTIONS: Inlet: 110 mm - Outlet: 103 mm
CD. 5500102212 12 V. Amp 11,5
CD. 5500102224 24 V. Amp 7,0

CAPACITY: 750 m3 per hour / 441 cfm
DIMENSIONS: 290 x 257 x 150 mm
PORT CONNECTIONS: Inlet: 150 mm - Outlet: 103 mm
CD. 5500102412 12 V. Amp 19
CD. 5500102424 24 V. Amp 11

CAPACITY: 1000 m3 per hour / 589 cfm
DIMENSIONS: 290 x 257x 180 mm
PORT CONNECTIONS: Inlet: 150 mm - Outlet: 103 mm
CD. 5500102624 24 V. Amp 16

DIMENSION:

